

Personal Protective Equipment for Froth-Pak™



Froth-Pak™ Foam Sealant

Used primarily as an air sealant, Froth-Pak™ Foam Sealant is a two-component, quick-cure polyurethane foam that quickly expands to fill cavities and is suited for gaps larger than 2" in:

- Wall/attic penetrations
- Electrical, mechanical and plumbing penetrations
- Attic hatch
- Attic perimeter, penetrations and ductwork
- Around can lights
- Vent pipe through roof
- Around pipes within wall cavities
- Gas lines
- HVAC penetrations
- Rim joists
- Top plates

Wear Personal Protective Equipment (PPE)

- NIOSH-approved full-face or half-mask air-purifying respirator with an organic vapor sorbent and a P100 particulate filter
- Protective clothing or impermeable coveralls including long sleeves for full body covering
- Chemical-resistant gloves (coated with nitrile, butyl rubber, neoprene or PVC)
- Goggles or safety glasses (unless using a full-face respirator)

Additional Information

Most frequently asked questions about Froth-Pak™ Foam Sealant are on the back side of this sign. Find additional information, videos and an Online Safe Handling tutorial at www.building.dupont.com. You may also contact DuPont at 1-866-583-2583. General information regarding the safe use of polyurethane foams can also be found at www.spraypolyurethane.org.





**For more information visit
frothpak.com
or call 1-866-583-2583**

NOTICE: No freedom from any patent owned by DuPont or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other government enactments. The product shown in this literature may not be available for sale and/or available in all geographies where DuPont is represented. The claims made may not have been approved for use in all countries or regions. DuPont assumes no obligation or liability for the information in this document. References to "DuPont" or the "Company" mean the DuPont legal entity selling the products to Customer unless otherwise expressly noted. NO EXPRESS WARRANTIES ARE GIVEN EXCEPT FOR ANY APPLICABLE WRITTEN WARRANTIES SPECIFICALLY PROVIDED BY DUPONT. ALL IMPLIED WARRANTIES INCLUDING THOSE OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED. The buyer assumes all risks as to the use of the material. Buyer's exclusive remedy or any claim (including without limitations, negligence, strict liability, or tort) shall be limited to the refund of the purchase price of the material. Failure to strictly adhere to any recommended procedures shall release DuPont Specialty Products USA, LLC or its affiliates, of all liability with respect to the materials or the use thereof. The information herein is not intended for use by non-professional designers, applicators or other persons who do not purchase or utilize this product in the normal course of their business.

CAUTION: This product is combustible. Protect from high heat sources. A protective barrier or thermal barrier may be required as specified in the appropriate building code. For more information, consult (Material) Safety Data Sheet ((M)SDS), call DuPont at 1-866-583-2583 or contact your local building inspector. In an emergency, call 1-989-636-4400 in the U.S. or 1-519-339-3711 in Canada.

WARNING: Rigid foam insulation does not constitute a working walkable surface or qualify as a fall protection product.

Froth-Pak™ Ultra Premium Foam Insulation contains isocyanate, hydrofluorocarbon blowing agent and polyol. Read all the instructions and (M)SDS carefully before use. Cover all skin. Wear protective clothing (including long sleeves), gloves, goggles or safety glasses, and proper full-faced respiratory protection. Do not breathe vapor or mist. Use only with adequate ventilation. It is recommended that applicators and those working in the spray area wear full-faced respiratory protection. Increased ventilation significantly reduces the potential for isocyanate exposure; however, supplied air or an approved full-faced air-purifying respirator equipped with an organic vapor sorbent and a particulate filter may still be required to maintain exposure levels below ACGIH, OSHA, WEEL or other applicable limits. For situations where the atmospheric levels may exceed the level for which an air-purifying respirator is effective, use a positive-pressure, full-faced air-supplying respirator (air line or self-contained breathing apparatus). Spraying large amounts of foam indoors may require the use of a positive pressure, full-faced air-supplying respirator. Contents under pressure.

DuPont™, the DuPont Oval Logo, and all trademarks and service marks denoted with ™, SM or ® are owned by affiliates of DuPont de Nemours, Inc. unless otherwise noted. © 2019 DuPont.

43-D100640-enNA-1119 CDP