

Safety Data Sheet

SOUDAL Soudafoam All Season Gun Grade

Section 1. Identification

Product Identifier SOUDAL Soudafoam All Season Gun Grade

Synonyms 455800 Manufacturer Stock 79302TN10

Numbers

Recommended use Refer to Technical Information
Uses advised against Refer to Technical Information

Manufacturer Contact

Address Soudal Accumetric 350 Ring RD

Elizabethtown, KY, 42701

USA

Phone Emergency Phone Fax

(270) 769-3385 (800) 424-9300 (270) 765-2412

CHEMTREC

Section 2. Hazards Identification

Classification ACUTE TOXICITY - DERMAL - Category 4

ACUTE TOXICITY - INHALATION - Category 4
ACUTE TOXICITY - ORAL - Category 4
CARCINOGENICITY - Category 2
EYE DAMAGE/IRRITATION - Category 2A
FLAMMABLE AEROSOLS - Category 1

SENSITIZATION - RESPIRATORY - Category 1A

SENSITIZATION - SKIN - Category 1

SKIN CORROSION/IRRITATION - Category 2

SPECIFIC TARGET ORGAN TOXICITY (Repeated Exposure) - Category 2 SPECIFIC TARGET ORGAN TOXICITY (Single Exposure) - Category 3

Signal Word Danger

Pictogram



Hazard Statements Causes serious eve irritation

Causes skin irritation

Extremely flammable aerosol

Harmful if inhaled Harmful if swallowed Harmful in contact with skin

May cause allergy or asthma symptoms or breathing difficulties if inhaled

May cause an allergic skin reaction

May cause damage to organs through prolonged or repeated exposure

(respiratory tract).

May cause respiratory irritation. Suspected of causing cancer.

Precautionary Statements

Response Call a poison center/doctor if you feel unwell.

Get medical advice/attention if you feel unwell.

If experiencing respiratory symptoms: Call a poison center/doctor.

If exposed or concerned: Get medical advice/attention. If eye irritation persists: Get medical advice/attention.

If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

If inhaled: If breathing is difficult, remove person to fresh air and keep

comfortable for breathing.

If on skin: Wash with plenty of soap and water.

If skin irritation or rash occurs: Get medical advice/attention. If swallowed: Call a poison center/doctor if you feel unwell.

Read label before use. If medical advice is needed, have product container or

label at hand. Rinse mouth.

Wash contaminated clothing before reuse.

Prevention Avoid breathing dust/fume/gas/mist/ vapors/spray.

Contaminated work clothing must not be allowed out of the workplace.

Do not eat, drink or smoke when using this product.

Do not handle until all safety precautions have been read and understood.

Do not spray on an open flame or other ignition source.

Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

Obtain special instructions before use.

Pressurized container: Do not pierce or burn, even after use.

Use only outdoors or in a well-ventilated area.

Wash thoroughly after handling.

Wear protective gloves/protective clothing/eye protection/face protection.

Wear respiratory protection.

Storage Protect from sunlight. Do not expose to temperatures exceeding 50C/122F.

Store in a well-ventilated place. Keep container tightly closed.

Store locked up.

Disposal Dispose of contents/container to in accordance with local/regional/national

/international regulations.

Ingredients of unknown

toxicity

0%

Hazards not Otherwise Classified

Other Hazards

Contains isocyanates. See information supplied by the manufacturer. Allergic sensitization may be possible with isocyanates. Persons already sensitized to diisocyanates may develop allergic reactions when using this product.

Section 3. Ingredients

CAS	Ingredient Name	Weight %
6425-39-4	Morpholine, 4,4'-(oxydi-2,1-ethanediyl)bis-	< 1 %
75-28-5	Isobutane	< 10 %
9016-87-9	Polymeric diphenylmethane diisocyanate	> 25 %
74-98-6	Propane	1% - 5%
	Coploymer	1% - 5%
8001-20-5	Tung oil	10% - 15%
115-10-6	Dimethyl ether	10% - 15%
13674-84-5	Trichorylpropylene Phophate	25% - 30%

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First-Aid Measures

Description of necessary

measures Inhalation

IF exposed or concerned: Get medical advice/attention; Call a POISON CENTER or doctor/physician. Get medical advice/attention if you feel unwell.

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician. Specific treatment (see label). If breathing is difficult, remove victim to fresh air and keep at rest in a position

comfortable for breathing. If experiencing respiratory symptoms:

Skin IF ON SKIN: Wash with plenty of soap and water. Call a POISON CENTER or

> doctor/physician if you feel unwell. Specific treatment (see ... on this label). Take off contaminated clothing and wash it before reuse. If skin irritation or

rash occurs: Get medical advice/attention.

Eyes IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing. If eye irritation persists:

Get medical advice/attention.

Ingestion IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel

unwell. Rinse mouth.

medical attention and special treatment needed

Indication of any immediate Treat symptomatically and supportively. Persons already sensitized to diisocyanates may develop allergic reactions when using this product. Most Important Symptoms/Effects Acute

Harmful if swallowed. Harmful in contact with skin. Harmful if inhaled. Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation.

Delayed

May cause allergic or asthmatic symptoms or breathing difficulties if inhaled. May cause allergic skin reaction. Suspected of causing cancer. May cause damage to organs through prolonged or repeated exposure: respiratory tract.

Section 5. Fire Fighting Measures

Suitable Extinguishing

Water, carbon dioxide

Media

Unsuitable Extinguishing

None known

Media

Special Hazards Arising

Extremely flammable aerosol.

from the Chemical

Oxides of carbon, Phosphorus oxides, hydrogen cyanide, hydrogen chloride.

Hazardous Combustion Products

May polymerize when heated.

Special Protective

Equipment and

Keep away from heat, sparks, open flame, and hot surfaces - No smoking. Do not spray on an open flame or other ignition sources. Do not pierce or burn, Precautions for Firefighters even after use. Wear full protective fire fighting gear including self contained

breathing apparatus (SCBA) for protection against possible exposure.

Fire Fighting Measures

Danger of explosion. Keep unnecessary people away, isolate hazard area and deny entry. Cool containers with water from unmanned hose holder or monitor nozzles until well after fire is out. Do not allow to enter into surface water or

drains.

Section 6. Accidental Release Measures

Personal Precautions, Protective Equipment and **Emergency Procedures**

Wear appropriate personal protective equipment recommended in Section 8 of the SDS. Do not smoke when using this product or handle near an open flame or sparks. Use explosion-proof electrical/ventilating/lighting equipment.

Methods and Materials for Containment and Cleaning

Do not pierce or burn, even after use.

Up

Environmental Precautions Do not allow to enter into surface water or drains. Dike for later disposal.

Section 7. Handling and Storage

Precautions for Safe Handling

Keep away from heat, sparks, open flame, and hot surfaces - No smoking. Do not spray on an open flame or other ignition sources. Do not pierce or burn, even after use. Wash thoroughly after handling. Do not eat, drink, or smoke when using this product. Wear protective gloves/clothing and eye/face protection. Take off contaminated clothing and wash before re-use. Contaminated work clothing should not be allowed out of the workplace. Do not breathe dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. [In case of inadequate ventilation] wear respiratory protection. Obtain special instructions before use. Do not handle until all

safety precautions have been read and understood. Use explosion-proof

electrical/ventilating/lighting equipment.

Conditions for Safe Storage, Including any Incompatibilities Store in a well-ventilated place. Keep container tightly closed.

Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding 50C/122F. Ensure adequate ventilation of the storage area. Maximum storage period

(time): 1 year.

Incompatible Materials Heat, strong acids, strong bases, Amines. Keep away from all ignition

sources.

Section 8. Exposure Controls/Personal Protection

Occupational Exposure Limits

ACGIH TLV	OSHA PEL	STEL
N/A	N/A	N/A
1000 ppm	N/A	1000 ppm
0.005 ppm	0.02 mg/m≈	N/A
1000 ppm TWA	1000 ppm PEL	N/A
N/A	N/A	N/A
N/A	N/A	N/A
N/A	400 ppm	N/A
N/A	N/A	N/A
	N/A 1000 ppm 0.005 ppm 1000 ppm TWA N/A N/A N/A	N/A N/A 1000 ppm N/A 0.005 ppm 0.02 mg/m≈ 1000 ppm 1000 ppm TWA PEL N/A N/A N/A N/A N/A N/A N/A 400 ppm

Personal Protective Equipment

Component Exposure Limits

Goggles, Gloves

Propane (74-98-6)

ACGIH:

1000 ppm TWA

NIOSH:

1000 ppm TWA; 1800 mg/m3TWA 2100 ppmIDLH (10% LEL)

OSHA (US):

1000 ppmTWA; 1800 mg/m3TWA

Isobutane (75-28-5)

ACGIH:

1000 ppm STEL

NIOSH:

800 ppmTWA; 1900 mg/m3TWA

Dimethyl ether (115-10-6)

Europe:

1000 ppm TWA; 1920 mg/m3 TWA

Biological limit value Engineering Controls There are no biological limit values for any of this product's components.

Use explosion-proof electrical/ventilating/lighting equipment. Keep away from

heat/sparks/open flames/hot surfaces.

Individual Protection Measures, such as Personal Protective Equipment Eye/face protection

Wear splash resistant safety goggles.

Skin Protection

Wear suitable protective clothing and gloves.

Respiratory Protection

Use a respirator with an organic vapor cartridge for concentrations exceeding

the occupational exposure limit.

Glove Recommendations

Recommended material type: LOW DENSITY POLYETHYLENE

Section 9. Physical and Chemical Properties

Physical State	Aerosol
Color	Champagne
Odor	Characteristic
Odor Threshold	Not available
Solubility	Soluble in
	organic
	solvents
Partition coefficient Water/n-octanol	Not available
VOC%	N/A
Viscosity	Not available
Specific Gravity	0.95
Density lbs/Gal	7.928
Pounds per Cubic Foot	59.307
Flash Point	Not available
FP Method	N/A
Ph	Not available
Melting Point	Not available
Boiling Point	Not available
Boiling Range	Not available
LEL	N/A
UEL	N/A
Evaporation Rate	Not available
Flammability	Not available
Decomposition Temperature	Not available
Auto-ignition Temperature	Not available
Vapor Pressure	Not available
Vapor Density	Not available

Note

The above information is not intended for use in preparing product

specifications. Contact Soudal Accumetric before writing specifications.

Section 10. Stability and Reactivity

Reactivity May polymerize when heated.

Chemical Stability Stable under normal conditions of use.

Possibility of Hazardous

Reactions

May polymerize when heated.

Conditions to Avoid Avoid contact with incompatible materials. Keep away from heat/sparks/open

flame/hot surfaces - No smoking. Do not spray on an open flame or other

ignition sources. Do not pierce or burn, even after use.

Heat, strong acids, strong bases, Amines, Keep away from all ignition Incompatible Materials

sources.

products

Hazardous decomposition Oxides of carbon, Phosphorus oxides, hydrogen cyanide, hydrogen chloride.

Section 11. Toxicological Information

Information on Likely Routes of Exposure

Inhalation

Harmful if inhaled. May cause allergic or asthmatic symptoms or breathing

difficulties if inhaled. May cause respiratory irritation.

Skin Contact

Harmful in contact with skin. Causes skin irritation. May cause allergic skin

reaction.

Eye Contact

Causes serious eye damage.

Ingestion

Harmful if swallowed.

Component Analysis -LD50/LC50

The components of this material have been reviewed in various sources and

the following selected endpoints are published:

2-Propanol, 1-chloro-, phosphate (3:1) (13674-84-5)

Oral LD50Rat 500 mg/kg

Dermal LD50Rabbit 1230 mg/kg Inhalation LC50Rat 5 mg/L 4 h

Isocyanic acid, polymethylenepolyphenylene ester (9016-87-9)

Inhalation LC50Rat 490 mg/m3 4 h

Propane (74-98-6)

Inhalation LC50Rat 658 mg/L 4 h

Isobutane (75-28-5)

Inhalation LC50Rat 658 mg/L 4 h

Dimethyl ether (115-10-6)

Inhalation LC50Rat 308.5 mg/L 4 h

Acute and Chronic Toxicity Immediate Effects

Harmful if swallowed. Harmful in contact with skin. Harmful if inhaled. Causes skin irritation. Causes serious eye irritation. May cause allergic or asthmatic symptoms or breathing difficulties if inhaled. May cause respiratory irritation.

Delayed Effects

Suspected of causing cancer. May cause allergic skin reaction. May cause damage to organs through prolonged or repeated exposure: respiratory tract.

Irritation/Corrosivity Data Causes skin irritation. Causes serious eye irritation. May cause respiratory

irritation.

Respiratory Sensitization May cause allergic or asthmatic symptoms or breathing difficulties if inhaled.

Dermal Sensitization May cause allergic skin reaction.

Component Isocyanic acid, polymethylenepolyphenylene ester (9016-87-9)

Carcinogenicity IARC:

Supplement 7 [1987]; Monograph 19 [1979](Group 3 (not classifiable))

DFG:

Category 4 (no significant contribution to human cancer)

Germ Cell Mutagenicity No data available Reproductive Toxicity No data available

Specific Target Organ Single Exposure: respiratory tract.

Toxicity Repeated Exposure: respiratory tract.

Aspiration Hazard No data available

Medical Conditions
Aggravated by Exposure

eye disorders, respiratory disorders, skin disorders, gastrointestinal disorders; May produce an allergic reaction. Persons already sensitized to diisocyanates may develop allergic reactions when using this product.

Section 12. Ecological Information

Component Analysis -

Aquatic Toxicity

2-Propanol, 1-chloro-, phosphate (3:1) (13674-84-5)

Fish:

LC50 96 h Brachydanio rerio 56.2 mg/L [static]; LC50 96 h Pimephales promelas 98 mg/L [static]; LC50 96 h Poecilia reticulata 30 mg/L [static]

Algae:

EC50 72 h Desmodesmus subspicatus 45 mg/L IUCLID; EC50 96 h

Pseudokirchneriella subcapitata 4 mg/L IUCLID

Invertebrate:

EC50 48 h Daphnia magna 63 mg/L IUCLID

Bioaccumulation No information available.

Mobility No information available.

Biodegradation Contains non readily biodegradable component(s).

Section 13. Disposal

Disposal Methods Dispose of contents/container in accordance with local/regional/national

/international regulations. Do not allow to enter into ground-water, surface

water or drains.

Section 14. Transport Information

UN Number 1950 **UN Proper Shipping Name Aerosols**

DOT Classification Hazard Class: 2.2 Required Label(s): 2.2

Packing Group None assigned

Section 15. Regulatory Information

U.S. Federal Regulations This material contains one or more of the following chemicals required to be

> identified under SARA Section 302 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65), CERCLA (40 CFR 302.4), TSCA 12(b), and/or require an

OSHA process safety plan.

Isocyanic acid, polymethylenepolyphenylene ester (9016-87-9)

SARA 313: 1 % de minimis concentration

SARA Section 311/312 (40 CFR 370 Subparts B and C)

Acute Health: Yes Chronic Health: Yes Fire: Yes Pressure: Yes Reactivity: Yes

U.S. State Regulations The following components appear on one or more of the following state

hazardous substances lists:

Isocyanic acid, polymethylenepolyphenylene ester (9016-87-9)

NJ

Propane (74-98-6) MA, MN, NJ, PA

Isobutane (75-28-5)

MA, NJ, PA

Dimethyl ether (15-10-6)

MA, MN, NJ, PA

Not listed under California Proposition 65

Canadian WHMIS

(IDL)

Components of this material have been checked against the Canadian Ingredient Disclosure List WHMIS Ingredients Disclosure List. The List is composed of chemicals which must be identified on SDSs if they are included in products which meet

WHMIS criteria specified in the Controlled Products Regulations and are

present above the threshold limits listed on the IDL:

Castor oil (8001-79-4) 1 %

WHMS Classification B5, D2A, D2B

Section 16. Other Information

Revision Date 3/17/2016

HMIS and NFPA Rating **HMIS**

> Health: 2* Fire: 3 Reactivity: 3

NFPA Health: 2 Fire: 3 Reactivity: 3 Hazard Scale:

- 0 = Minimal
- 1 = Slight
- 2 = Moderate
- 3 = Serious
- 4 = Severe
- * = Chronic hazard

Disclaimer

The data contained herein is based upon information that Soudal Accumetric believes to be reliable. Users of this product have the responsibility to determine that suitability of use and to adopt all necessary precautions to ensure the safety and protection of property and persons involved in said use. All statements or suggestions are made without warranty, expressed or implied, regarding the accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof.