

MATERIAL SAFETY DATA SHEET

NOTE: BLANK SPACES ARE NOT	PERMIT	TED. IF ANY ITEM	I IS NOT APPLICABLE	, THE SPACE MUS	ST BE MARKEI	D TO INDICATE THAT
IDENTITY				PART NO.		
(As Shown On Label Or Package)	F-907 22oz	Plasti Dip		IF APPLICAT	BLE	
SECTION I						
MANUFACTURER'S				EMERGENC	Y PHONE No.	
NAME Plasti Dip Intern				USA only: 1-8	00-424-9300 IN	IT'L: 703-527-3887
ADDRESS (NUMBER, STREET, CI	TY, STATI	E AND ZIP CODE)		REVISION #		
3920 Pheasant Ridge Drive						
					URER'S PHONE	
Blaine, MN 55449					ORMATION 1-	763-785-2156
				DATE MSDS	DED Db.	- 10, 2000
CECTION W. WAZARRONG WICH	IDITIALIZA I	NEODMARTON	11 TY 12 TY 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		RED Decembe	
SECTION II - HAZARDOUS INGRE carcinogens if 0.1% of the composition			II Health Hazards which	comprise 1% or gre	eater of the comp	position and all
HAZARDOUS COMPONENTS CH		% Wt.	CAS NO.	OSHA	ACGIH	OTHER LIMITS
and IDENTITY AND COMMON N		(OPTIONAL)	CAS NO.	PEL	TLV	RECOMMEND
VM&P Naphtha	AME (b)	36–38	64742-89-8	300 ppm	300 ppm	None
Heptane		18-20	426260-76-6	500 ppm	400 ppm	None
Toluene		14 – 16	108-88-3	200 ppm	50 ppm	None
Methyl Ethyl Ketone		3 – 5	78-93-3	200 ppm	200 ppm	None
Resins		2 2	N/A	N/A	N/A	None
Carbon Black			133-86-4	3.5 mg/m ³		None
SECTION III - PHYSICAL / CHEM	ICAL CHA	RACTERISTICS	<u> </u>			<u>.</u>
BOILING		FIC GRAVITY (H ₂ 0	=1)	APPROXIMA	TE WEIGHT P	ER GALLON (LBS)
POINT N/E		.79	· ·	6.62		
VAPOR PRESSURE	VAPOF	R DENSITY		EVAPORATI	ON RATE	
125 mmHg @ 20°C	(AIR =	 Heavier than air 		(BUTYL ACE	TATE = 1) >1.	0
SOLUBILITY IN WATER	% VOL	ATILE 79.6		OTHER		
Insoluble	VOC L	BS./GAL 5.27		(IF ANY) No	one	
APPEARANCE						
		stance – Characteristi	c Odor			
SECTION IV-FIRE AND EXPLOSION	ON HAZAF	RD DATA				
FLASH POINT 15°F		FLA	MMABLE LIMITS	LEL	U	EL
(METHOD USED) TCC				0.9		11.5
EXTINGUISHING						
MEDIA Carbon Dioxide, D	ry Chemica	l, or Foam				
SPECIAL FIRE			C 11 C			
FIGHTING PROCEDURES Self co	ntained brea	athing apparatus with	a full face piece, operated	in pressure demand	or other positive	pressure mode.
UNUSUAL FIRE AND	: _1 :_ £1		:			
EXPLOSION HAZARDS This mate HAZARDOUS PRODUCTS FORME		nable and may be igni	ned by neat, sparks, name	or static electricity.		
FIRE OR THERMAL DECOMPOSI		arbon Dioxide and/or	Carbon Monovide			
EXPLOSIVE LIMITS	11011	aroon Brownee and/or	Curbon Wonoxide			
(% BY VOLUME IN AIR) 0.9 – 11	.5					
SECTION V - OPTIONAL HAZARI		S IDENTIFICATION	N			
HAZARD RATING			National Fire Protectio	n Association (NFP	A)	
4-EXTREME					/	
3-HIGH			FIRE 3 REACTIV	TTY <u>0 .</u>		
2-MODERATE						
1-SLIGHT						
0-INSIGNIFICANT			HEALTH 2 SPE	CIAL HAZARDS _	None .	
**SEE SECTION IV						

This is the "front" when printed in duplex. Page 1 of 2 pages if not duplex.



SECTION VI - REACTIVITY	AND STABILITY DATA		
STABILITY UNSTAF	BLE STABLE X		
INCOMPATIBILITY (Materia	als to Avoid) Strong acids, bases, oxidizing	agents, selected amine	es with alkali metals and halogens.
HAZARDOUS DECOMPOSIT	FION OR BY PRODUCTS Carbon Monoxid	de, Carbon Dioxide	-
HAZARDOUS	MAY OCCUR	CONDITIONS TO	AVOID
POLYMERIZATION	WILL NOT OCCUR X	May be ignited by he	at, sparks, flame or static electricity.
SECTION VII - HEALTH HA	ZARD DATA		
ROUTES OF ENTRY	INHALATION? YES SKIN? YE	S INGESTION:	? YES EYES? YES
HEALTH ACUTE	X		
HAZARDS CHRONIC	X		
CARCINOGENICITY: No			
SIGNS AND			
SYMPTOMS OF	Headache, Dizziness, Drowsiness, Fatigue, I	Irregular Heartbeat, Sk	in and Eye Irritation.
EXPOSURE			
MEDICAL CONDITIONS GE	NERALLY AGGRAVATED BY EXPOSU	RE	
EMERGENCY AND	Ingestion: Contact Physician or Poison Con		
FIRST AID	Inhalation: Remove to fresh air. Administer	70	· ·
PROCEDURES	Eye Contact: Flush with large amounts of w	vater. If irritation pers	ists, contact Physician.
	Skin: Wash with soap and water.		
SECTION VIII - PRECAUTIO	ONS FOR SAFE HANDLING AND USE		
STEPS TO BE TAKEN	Wipe up with floor absorbent. Transfer to h		
IN CASE MATERIAL IS	·		below PEL's. Use sand or other material to dam or contain
RELEASED OR SPILLED	spills. If large spill, notify appropriate state	and local agencies.	
WALEST PAGE OF A		1	
WASTE DISPOSAL METHOI	DS Dispose of product in accordance with loc	al, county, state and fo	ederal regulations.
DDECA HEIONG TO DE	A 11 4 14 T	1 1 77 % 1	, , , , , , , , , , , , , , , , , , ,
PRECAUTIONS TO BE	sources and store in a cool area. Avoid inha		equate ventilation. Keep away from sparks, flame and heat
TAKEN IN HANDLING AND STORAGE	Use good personal hygiene practices.	nation of vapors and p	ersonal contact with figure product.
ANDSTORAGE	Ose good personal hygiene practices.		
OTHER	Keen Container Closed When Not In Use (Containers should be d	isposed of in an environmentally safe manner in accordance
PRECAUTIONS	with Governmental Regulations.		
SECTION IX - CONTROL MI	e		
	ON (SPECIFY TYPE) Depending on the Airbo	orne concentration.	PROTECTIVE GLOVES
	e NIOSH approved cartridge or supplied air eq		Impervious Gloves
	EXHAUST Supplemental (if needed)		SPECIAL None
	NICAL (GENERAL) To maintain exposure	below PEL's	OTHER None
EYE PROTECTION			OTHER PROTECTIVE CLOTHING OR EQUIPMENT
Chemical splash goggles, or appr	roved eye protection.		Chemcial Apron/Eye bath/Safety Shower
WORK HYGIENIC PRACTIC	CES Wash thoroughly after handling.		
SECTION X - TRANSPORTA	TION INFORMATION		
DOT PROPER SHIPPING NA	ME Coating Solution	DOT HAZARD C	LASS 3
DOT UN NUMBER UN 1139		DOT PACKING	
IATA PROPER SHIPPING NA		IATA HAZARD (
IATA UN NUMBER UN 1139	·	IATA PACKING	
SECTION XI - 313 SUPPLIER		•	
		ECT TO REPORTIN	G REQUIREMENTS OF SECTION 313 OF THE
			R 372, (see table on page 1 for CAS # and percent by weight).
Heptane, Toluene, and Methyl E			, , I
	•	THE STATE OF C	ALIFORNIA TO CAUSE CANCER AND BIRTH
DEFECTS, OR OTHER REPR			

This is the "back" when printed in duplex. Page 2 of 2 pages if not duplex.

Prepared By Michael N. Hindin			
	Prepared By	Michael N Hindin	