



\*Estimate N/A-Not Applicable N/R-Not Restricted N/E-Not Established

## **MATERIAL SAFETY DATA SHEET**

NOTE: BLANK SPACES ARE NOT I	PERMITTI	ED. IF ANY ITEN	M IS NOT APPLICABLE	, THE SPACE M	UST BE MARK	KED TO INDICATE THAT.		
IDENTITY				PART NO.				
(As shown on Label or package) VLP	(F-631)	IF APPLICABLE						
SECTION I								
MANUFACTURER'S				EMERGENCY PHONE No.				
NAME Plasti Dip Interna				USA only: 1-8	USA only: 1-800-424-9300 INT'L: 703-527-3887			
ADDRESS (NUMBER, STREET, CIT	Y, STATE	AND ZIP CODE)		REVISION #	REVISION # 0003			
3920 Pheasant Ridge Drive								
		MANUFACTURER'S PHONE						
Blaine, MN 55449				No. FOR INFORMATION 1-763-785-2156				
		DATE MSDS						
			WAS PREPARED March 25, 2010					
SECTION II - HAZARDOUS INGREI			Il Health Hazards which	comprise 1% or g	reater of the co	mposition and all		
carcinogens if 0.1% of the composition			CACNO	OCHA	ACCITI			
HAZARDOUS COMPONENTS CHE		% Wt.	CAS NO.	OSHA PEL	ACGIH TLV	OTHER LIMITS  PECOMMEND		
and IDENTITY AND COMMON NA Tetrahydrofuran	IVIE (5)	(OPTIONAL) 60.3	109-99-9	200 ppm	200 ppm	RECOMMEND None		
Methyl Ethyl Ketone		18.9	78-93-3	200 ppm	200 ppm	None		
Cyclohexanone		2.4	108-94-1	50 ppm	25 ppm	None		
Cyclonicamonic		2.4	100-74-1	эо ррш	23 ppiii	TYOHC		
SECTION III - PHYSICAL / CHEMIC	CAL CHAR	ACTERISTICS		1	<u> </u>	ı		
BOILING		C GRAVITY (H <sub>2</sub> 0	) –1)	APPROXIMA	TE WEIGHT	PER GALLON (LBS)		
<b>POINT</b> 151 – 175°F	or Learn	0.90 -		7.65				
VAPOR PRESSURE	VAPOR	DENSITY	***	EVAPORATION RATE				
143 mmHg @ 20°C		Heavier than air		(BUTYL ACETATE =1) >1.0				
SOLUBILITY IN WATER	% VOLATILE 81.6			OTHER				
insoluble	VOC LBS./GAL 6.2			(IF ANY)				
APPEARANCE								
AND ODOR Clear liquid, strong solv	ent odor							
SECTION IV-FIRE AND EXPLOSION	N HAZARI	) DATA						
FLASH POINT 6.0°F		FL	FLAMMABLE LIMITS		1	UEL		
(METHOD USED) TCC				1.3		11.8		
EXTINGUISHING								
MEDIA Carbon Dioxide, Dry	Chemical,	or Foam						
SPECIAL FIRE								
FIGHTING PROCEDURES Self con	tained breat	hing apparatus with	a full face piece, operated	in pressure deman	d or other positiv	ve pressure mode.		
UNUSUAL FIRE AND								
EXPLOSION HAZARDS This materi		able and may be ign	nited by heat, sparks, flame	or static electricity	•			
HAZARDOUS PRODUCTS FORMED		de la Dienii 1	Cardaan Mar					
FIRE OR THERMAL DECOMPOSIT EXPLOSIVE LIMITS	IUN Cai	roon Dioxide and/o	r Carbon Monoxide					
(% BY VOLUME IN AIR) 1.3 – 11.8								
SECTION V - OPTIONAL HAZARD	RATINCS	IDENTIFICATIO	N					
HAZARD RATING	катпиоз.	IDENTIFICATIO		on Association (N	EDA)			
4-EXTREME			National Fire Protection	on Association (N	rra)			
3-HIGH	FIRE 3 REACTIVITY 0.							
2-MODERATE		<u></u>						
1-SLIGHT								
0-INSIGNIFICANT	HEALTH 2 SPECIAL HAZARDS None.							
**SEE SECTION IV								

This is the "front" when printed in duplex. Page 1 of 2 pages if not duplex.



SECTION VI -	REACTIVIT	Y ANI	O STABILITY DATA						
STABILITY UNSTABLE STABLE X									
INCOMPATIB	ILITY (Mater	ials to	Avoid) Strong acids, base	s, oxidizing ag	ents, selected amines	s with alkali metals and halogens.			
HAZARDOUS DECOMPOSITION OR BY PRODUCTS									
HAZARDOUS		MA	Y OCCUR	CO	ONDITIONS TO AVOID				
POLYMERIZA	TION	WIL	L NOT OCCUR X	Ma	ay be ignited by heat, sparks, flame or static electricity				
SECTION VII - HEALTH HAZARD DATA									
ROUTES OF E	NTRY	INH	ALATION? YES	SKIN? YES	INGESTION?	YES EYES? YES			
HEALTH	ACUTE	X							
HAZARDS	CHRONIC	X							
CARCINOGEN	ICITY: No								
SIGNS AND									
SYMPTOMS O	F	Head	ache, Dizziness, Drowsiness, Fatigue, Irregular Heartbeat, Skin and Eye Irritation.						
EXPOSURE									
MEDICAL CO.	UDITIONIC C	ENED	ATTACA CODATA TED	DAY EXPOSEIT					
MEDICAL CO	NDITIONS G	ENEK	ALLY AGGRAVATED	BY EXPOSUE	<u>CE</u>				
EMEDGENCY	AND	T.,	-ti Ctt Dhi-i	. D.: C	-1 T 4! -41				
EMERGENCY FIRST AID	AND		Ingestion: Contact Physician or Poison Control Immediatley.  Inhalation: Remove to fresh air. Administer Oxygen or Artificial Respiration if Necessary.						
PROCEDURES	!		Contact: Flush with large			· ·			
FROCEDURES	•		: Wash with soap and wat		ier. II iiiitation persi	ists, contact Fhysician.			
SECTION VIII	- PRECAUTI		OR SAFE HANDLING						
SECTION VIII	- I KECAUTI	ONSI	OK SAFE HANDLING	HILD USE					
STEPS TO BE	TAKEN	Wine	e up with floor absorbent.	Transfer to hoo	od Prevent run-off to	o sewers			
IN CASE MAT			nate all sources of ignition. Ventilate to maintain exposure below PEL's. Use sand or other material to dam or contain						
RELEASED OF			s. If large spill, notify app			or and the second of the secon			
			3-1 , , , , , , , ,		8				
WASTE DISPO	SAL METHO	DDS D	rispose of product in accord	dance with loca	al, county, state and f	federal regulations.			
PRECAUTION	S TO BE	Avoi	d eye contact with eyes. K	eep container	ntainer closed. Use with adequate ventilation. Keep away from sparks, flame and heat				
TAKEN IN HA	NDLING	Sour	Sources and store in a cool area. Avoid inhalation of vapors and personal contact with liquid product.						
AND STORAG	E	Use	good personal hygiene prac	ctices.					
OTHER	_				ntainers should be di	isposed of in an environmentally safe manner in accordance			
PRECAUTION			Governmental Regulations	3.					
SECTION IX -						1			
			PECIFY TYPE) Dependin			PROTECTIVE GLOVES			
VENTILATION			SH approved cartridge or s UST Supplemental (if ne		пршеш.	Impervious Gloves  SPECIAL None			
VENTILATION			(GENERAL) To maint		alaw DEL la	OTHER None			
EYE PROTECT		NICAL	(GENERAL) TO Maint	ani exposure o	CIOW FEL S	OTHER PROTECTIVE CLOTHING OR EQUIPMENT			
		nroved	eve protection			Chemcial Apron/Eve bath/Safety Shower			
	Chemical splash goggles, or approved eye protection.  WORK HYGIENIC PRACTICES Wash thoroughly after handling.  Chemical Apron/Eye bath/Safety Shower								
			N INFORMATION	anding.					
					DOT HAZARI	CLASS 3			
DOT PROPER SHIPPING NAME Coating Solution DOT UN NUMBER UN1139					DOT PACKING GROUP II				
IATA PROPER SHIPPING NAME Coating Solution					IATA HAZARD CLASS 3				
IATA UN NUMBER UN 1139					IATA PACKING GROUP II				
SECTION XI - 313 SUPPLIER NOTIFICATION									
THIS PRODUCT CONTAINS THE FOLLOWING CHEMICALS SUBJECT TO REPORTING REQUIREMENTS OF SECTION 313 OF THE									
						<b>R 372,</b> (see table on page 1 for CAS # and percent by weight).			
Methyl Ethyl Ketone									
WARNING: THIS PRODUCT CONTAINS A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND BIRTH									
DEFECTS OF	OTHED DED	DODI	ICTIVE HADM						

This is the "back" when printed in duplex. Page 2 of 2 pages if not duplex.

Prepared By: Mark Kenow	
-------------------------	--